

Via D. Alighieri 33 29010 Villanova sull'Arda (PC) - Italy Tel. 0039.0523.837899 Fax 0039.0523.837381

回数回 第699

Data Sheet

UNI EN ISO 9001-2008 Certified Company







K-FLEX 3000 H.F

Description: Halogen free multi cores flexible control and connecting cable. Design: Flexible bare copper conductors according to CEI 20-29 Class 5 and DIN-VDE 0295 K5 Halogen free insulation compound type TI6 according to HD 21.14 S1 annex A Construction: Black numbered cores with or without green yellow core Halogen free jacket compound type TM7 according to HD 21.14 S1 annex B Manufacturing's Test and Control according to our certificated ISO 9001-2008 CSQ-IMQ (EQ-NET) Quality Controls: System procedure. Labor tests reports are stored in our internal Q.C. laboratory archive together with the production reports Norms: Flame-retardant according to IEC 60332-1-2 (flame spread on a single cable) No flame-propagation according to IEC 60332-3-24 respectively IEC 60332-3-25 (Flame spread on vertical cable or wire bundle) Halogen-free according to IEC 60754-1 (amount of halogen acid gas) Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity) Low smoke density according to IEC 61034-2 CPR classification: Dca, s2, d2, a1 (It satisfies the non-flame propagation test, with the requirement of non-fire propagation and with emitted heat limits for this class). The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE Technical dates: Nominal voltage: 300/500V 3000 V Spark Test voltage: Working temperature: Occasional flexing: -15°C to +70°C Fixed installation: -40°C to +70°C Occasional flexing: 15 x outer Ø Minimum bending radius Fixed installation: $4 \times \text{outer } \emptyset$ Use: Environmentally friendly, halogen-free Control Cable especially for electrical equipment and installations in industrial environments, dry or damp interiors. Suitable for fixed installation under medium mechanical load conditions as well as for flexing

application at free, non-continuously recurring movement without tensile load or compulsory guidance. Outdoor use with UV-protection only, considering the temperature range. Not for

Particularly suitable where human and animal life as well as valuable property are exposed to

direct burial.

high risk of fire hazards