



## K-FLEX 3000 C H.F. UL CSA

**Description :** American, EMC-compliant Halogen Free Control Cable with improved characteristics in case of fire.

**Design:**



**Construction :** Flexible bare copper conductors according to CEI 20-29 Class 5, IEC 60228 Cl.5 and DIN-VDE 0295 K5  
 Halogen free insulation compound type TI6 according to HD 21.14 S1 annex A  
 Black numbered cores with or without green yellow core  
 Halogen free inner jacket compound type **TM7** acc. to HD 21.14 S1 annex B  
 Tinned copper screening with coverage 85% ± 5%  
 Halogen free outer jacket compound type **TM7** acc. to HD 21.14 S1 annex B

**Manufacturing's Controls:** Test and Control according to our certificated **ISO 9001-2015 CSQ-IMQ (EQ-NET)** Quality System procedure.

Labor tests reports are stored in our internal Q.C. laboratory archive together with the production reports

**Norms :**

Flame-retardant according to IEC 60332-1-2  
 No flame-propagation according to IEC 60332-3-24 respectively IEC 60332-3-25  
 UL Flame rating: FT2  
 Halogen-free according to IEC 60754-1  
 Corrosiveness of combustion gases according to IEC 60754-2  
 Low smoke density according to IEC 61034  
 According to UL style 10615 and 21217 and CSA-AWM I A/B II A/B  
 The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE

**Technical dates :**

- Nominal voltage : 600V
- Spark Test voltage : 6000 V
- Working temperature : Occasional flexing: -15°C to +75°C  
Fixed installation: -40°C to +75°C
- Minimum bending radius Occasional flexing: 20 x outer Ø  
Fixed installation: 6 x outer Ø

**Use :** Environmentally friendly, halogen-free Control Cable especially for electrical equipment and installations in industrial environments, dry or damp interiors.  
 Suitable for fixed installation under medium mechanical load conditions as well as for flexing application at free, non-continuously recurring movement without tensile load or compulsory guidance. Outdoor use with UV-protection only, considering the temperature range. Not for direct burial.  
 Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards range. Particularly suitable where human and animal life as well as valuable property are exposed to high risk of fire hazards