



K-FLEX 3100 P UL CSA

Description : American and Canadian approved, increased oil-resistant Control and Power supply single core cables, conforming to UL AWM Style 11624.

Design:



Construction : Flexible bare copper conductors according to CEI 20-29 Class 5, IEC 60228 Cl.5, DIN-VDE 0295 K5 and UL 83 standard
 Special PVC Insulation compound type TI3 UL 90°C 758
 Black or Green Yellow coloured core
 Outer sheath in special Flame Retardant PUR compound according UL 80°C 758

Manufacturing's Controls: Test and Control according to our certificated **ISO 9001-2015 CSQ-IMQ (EQ-NET)** Quality System procedure.
 Labor tests reports are stored in our internal Q.C. laboratory archive together with the production reports

Norms : Flame retardant, according to IEC 60332-1.
 Oil Resistant according EN 60811-1-2:1995
 Flame-retardant according to CSA FT1
 According to UL styles 11624 and CSA-AWM I/II A/B
 The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE

Technical dates :	<ul style="list-style-type: none"> • Nominal voltage: 1.000 V • Spark Test voltage: 10.000 V • Fixed installation working temperature: -40°C to + 80°C Occasional flexing working temperature: -5°C to + 80°C • Fixed installation minimum bending radius = 4 x cable Ø Occasional flexing minimum bending radius = 13 x cable Ø
--------------------------	--

Use : These power single core cables are especially suitable for export-orientated machinery. It is suitable for control equipment on machine tools subjected to medium mechanical stresses, for fixed or flexible installation, where free movement is required without tensile stresses and without forced guidance systems, in dry, damp and wet interiors (including water-oil mixtures).