



K-PLUS 8000 CP POWER UL CSA

Description : Chain application American and Canadian control and power shielded cable EMC-compliant, PVC insulated numbered cores and PUR outer sheath.

Design:



Construction : Extra Flexible bare copper conductors according to CEI 20-29 Class 6 and DIN-VDE 0295 K6 Special PVC Insulation compound type **TI1** according to UL 758 80°C, CEI 20-11 and VDE 0207
 Black numbered cores + green yellow core.
 Nonwoven tape over the outer layer
 Inner jacket in special PVC **TM2** according to CEI 20-11 and VDE 0207
 Tinned copper screening with coverage 85% ± 5%
 Nonwoven tape
 Special PUR outer sheath, matt and low adhesive surface according UL 758 and UL 1581

Manufacturing's Controls: Test and Control according to our certificated **ISO 9001-2015 CSQ-IMQ (EQ-NET)** Quality System procedure.
 Labor tests reports are stored in our internal Q.C. laboratory archive together with the production reports

Norms : Flame retardant, according to IEC 60332-1.
 Oil Resistant according EN 60811-1-2:1995
 According to UL styles 20940 and CSA-AWM I A/B II A/B
 Flame-retardant according to CSA FT1
 The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE

Technical dates :

- Nominal voltage : 1.000 V UL - 600/1.000 V. IEC
- Spark Test voltage : 10.000 V
- Working temperature: Flexing: -15°C to +80 °C
 Fixed installation: -40 °C to +80 °C
- Minimum bending radius: For flexible use: 8 x outer diameter
 Fixed installation: 4 x outer diameter

Use : Internationally approved this cable is suitable to be used in power chains or moving machine parts as link and connection control cable. Designed for 5 million alternating bending cycles and horizontal travel distances up to 10 meter. Predominantly installed in dry, damp or wet environments. If considering the temperature range it can be used outdoors too. The copper braid serves as electromagnetic screen between the internal electric circuits and the environment.