



## K-PLUS 9000 P POWER

**Description :** Chain application, TPE insulated and PUR sheathed power supply and control cable manufactured for working voltage of 600/1000V.

**Design:**



**Construction :** Extra Flexible bare copper conductors according to CEI 20-29 Class 6 and DIN-VDE 0295 K6  
TPE polypropylene based elastomer insulation compound  
Black numbered cores + GY core  
Nonwoven tape over the outer layer  
Special PUR outer sheath, matt and low adhesive surface

**Manufacturing's Controls:** Test and Control according to our certificated **ISO 9001-2015 CSQ-IMQ (EQ-NET)** Quality System procedure.  
Labor tests reports are stored in our internal Q.C. laboratory archive together with the production reports

**Norms :** High oil-resistance - Abrasion and notch-resistant - Low-adhesive surface  
Resistant to hydrolysis and microbes  
Ozone resistant according VDE 0472 part 805 and UV resistant according HD 605 A1  
Halogen-free according to IEC 60754-1 (amount of halogen acid gas)  
Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)  
Low smoke density according to IEC 61034  
The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE

**Technical dates :**

- Nominal voltage : 600/1000 V
- Spark Test voltage : 6000 V
- Working temperature : Flexing: -40°C to +80°C  
Fixed installation: -50°C to +90°C
- Minimum bending radius : For flexible use: 6 x outer diameter  
Fixed installation: 3 x outer diameter

**Use :** Designed for up to 4 million bending/unbending cycles inside power chains. For travel distances up to 60 mt.  
Suitable for use in power chains, moving machine parts, particularly in wet or oil contaminated areas of machine tools and transfer lines.  
Suitable for use in measuring, control and regulating circuits so as in wiring of machines, tools, devices, appliances and control cabinets. Suitable for outdoor use within the indicated operating temperature range.