



## K-SERVO PLUS 3500 9Y CY O.R. UL CSA

**Description :** Drag chain application, Oil Resistant, UL AWM approved, EMC-compliant, Low capacity screened motor connection cable with black coded cores, 0.6/1kV.

**Design:**



**Construction :**

- Extra Flexible bare copper conductors according to CEI 20-29 Class 6 and DIN-VDE 0295 K6
- Special PP Thermo-Plastic insulation compound
- Black coded cores ( U/L1/C/L+ ; V/L2 ; W/L3/D/L ) + GY core
- Nonwoven Tape
- Tinned copper wires braiding with coverage 85%
- Nonwoven Tape
- Special PVC outer sheath compound 80°C type TM5 Oil Resistant according to CEI 20-11, VDE 0207 and UL 758

**Manufacturing's Controls:** Test and Control according to our certificated **ISO 9001-2015 CSQ-IMQ (EQ-NET)** Quality System procedure.  
Labor tests reports are stored in our internal Q.C. laboratory archive together with the production reports

**Norms:** Flame retardant, Test method B according to DIN VDE 0472 part 804, IEC 60332-1, IEC 60332-3-24 and CSA FT1  
Oil-resistant according to EN 50363-4-1: TM5  
According to UL styles 2570 and CSA-AWM I A/B II A/B  
The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE

**Technical dates :**

- Nominal voltage : 1.000V.
- Spark Test voltage : 6000 V
- Working temperature: Flexing: -5°C to +80°C  
Fixed installation: -40°C to +80°C
- Minimum bending radius Occasional flexing: 8 x outer Ø  
Fixed installation: 4 x outer Ø

**Use :** Servo motors cables are suitable wherever drives form a single unit together with cable, frequency converter and motor, and the potential for electromagnetic interference is high because of this. Suitable for Automotive systems, Machine tool manufacturing, Production plants.  
This cable is suitable to be used in power chains or moving machine parts as link and connection control cable. It's suitable for up to 6 million bending/unbending cycles in the power chain applications. For travel distances up to 10 mt. Predominantly installed in dry, damp or wet environments.  
This cable is suitable to be used in power chains or moving machine parts as link and connection control cable. It's suitable for up to 6 million bending/unbending cycles in the power chain applications. For travel distances up to 10 mt. Predominantly installed in dry, damp or wet environments.