



K-SERVO PLUS 3500 9Y CY

Description : Drag chain application, EMC-compliant, Low capacity screened motor connection cable with black coded cores, 0.6/1kV.

Design:



Construction : Extra Flexible bare copper conductors according to CEI 20-29 Class 6 and DIN-VDE 0295 K6
Special PP Thermo-Plastic insulation compound
Black coded cores (U/L1/C/L+ ; V/L2 ; W/L3/D/L) + GY core
Nonwoven Tape
Tinned copper wires braiding with coverage 85%
Nonwoven Tape
PVC outer sheath compound 70°C type TM2 according to CEI 20-11, VDE 0207

Manufacturing's Controls: Test and Control according to our certificated **ISO 9001-2015** CSQ-IMQ (EQ-NET) Quality System procedure.

Labor tests reports are stored in our internal Q.C. laboratory archive together with the production reports

Norms: Flame retardant, Test method B according to DIN VDE 0472 part 804, IEC 60332-1
Oil resistant according: DIN EN 50290-2-22 resp. VDE 0819-102, TM54.
The cable is conform to Low Voltage Directive (LVD) 2014/35/EU CE

Technical dates :

- Nominal voltage : 1.000V.
- Spark Test voltage : 6000 V
- Working temperature: Flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C
- Minimum bending radius Occasional flexing: 8 x outer Ø
Fixed installation: 4 x outer Ø

Use : Servo motors cables are suitable wherever drives form a single unit together with cable, frequency converter and motor, and the potential for electromagnetic interference is high because of this. Suitable for Automotive systems, Machine tool manufacturing, Production plants.

This cable is suitable to be used in power chains or moving machine parts as link and connection control cable. It's suitable for up to 6 million bending/unbending cycles in the power chain applications. For travel distances up to 10 mt. Predominantly installed in dry, damp or wet environments.